

Hand Chain Block

- Each hoist is made with high performance materials for extra durability.
- The sealed bearings in each unit ensure extra protection and allow complete repair flexibility.
- Black painted finish calibrated load chain & Electro galvanised hand chain.
- Top and bottom hooks with heavy duty cast catches.
- Available in a variety of heights of lift.
- Also available in Black gloss finish for theatre rigging.
- For heights of lift above 12 mtrs please consult SWL for technical advice and product guidance.



W.L.L	a	b	c	d	h	Load Chain Dia.	No of Falls	Effort Req to Lift Max Load	Weight
kgs	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(N)	(Kgs)
500	148	132	23	35	345	6	1	240	9.3
1,000	172	151	26	40	376	6	1	250	12.2
1,500	196	173	29.5	45	445	7	1	265	16.5
2,000	210	175	34	50	470	8	1	335	19.5
3,000	255	205	37.5	55	580	10	1	372	35
5,000	280	189	41	65	690	10	2	380	43
10,000	463	189	51	85	830	10	4	380	80.7
20,000	630	200	80	110	1,000	10	8	400 x 2	180



SWL Rope Lifting & Testing, 4 Monza House, Third Avenue, Millbrook, Southampton, SO15 0LD

Telephone: 02380 338286

Email: sales@swl.org.uk