Polyester Round Sling

- Conform to BS EN1492-2 and 'Machinery Directive 2006/42/EC'
- Factor of Safety: 7:1
- Manufactured with 100% High Tenacity Polyester
- High Strength to Weight Ratio
- Light and Flexible, that's twist and kink resistant
- Marked with Manufacturer, SWL, Length and ID Mark
- Available in Black Colour for Theatre Industry



EWL (Effective Working Length)	1 Tonne Violet 50mm	2 Tonne Green 52mm	3 Tonne Yellow 60mm	4 Tonne Grey 70mm	5 Tonne Red 80mm	6 Tonne Brown 90mm	8 Tonne Blue 104mm	10 Tonne Orange 110mm
500mm	RS11	RS21	RS31	RS41	RS51	RS61	RS81	RS101
1mtr	RS12	RS22	RS32	RS42	RS52	RS62	RS82	RS102
1.5mtr	RS13	RS23	RS33	RS43	RS53	RS63	RS83	RS103
2mtr	RS14	RS24	RS34	RS44	RS54	RS64	RS84	RS104
2.5mtr	RS15	RS25	RS35	RS45	RS55	RS65	RS85	RS105
3mtr	RS16	RS26	RS36	RS46	RS56	RS66	RS86	RS106
4mtr	RS18	RS28	RS38	RS48	RS58	RS68	RS88	RS108



SWL Rope Lifting & Testing, 4 Monza House, Third Avenue, Millbrook, Southampton, SO15 0LD

Telephone: 02380 338286

Rope Lifting & Testing Ltd Email: sales@swl.org.uk